


Weighing



DVWS

DIMENSIONING | WEIGHING | SCANNING



2.5 kg

Application areas:

- Distribution Center
- Bulk Mail Center
- Warehouse
- Product data acquisition for invoicing, Revenue Recovery and Revenue Protection

System advantages:

- 100% in-line control during and / or directly after the preliminary process
- Completeness check
- Quality improvement
- Real time data transparency
- Manifesting
- Weighing in extreme environments
- Acquisition of the data from every posted item
- Verification of process data
- Higher performance

Type	EC-M-SL, HC-SL, HC-FL
Weighing Conveyor	600 mm x 400 mm; 1.800 mm x 1.000 mm (*)
Weighing System	Electro Magnetic Force Restoration
Resolution	6 kg/1 g; 12 kg/2 g; 30 kg/5 g; 60 kg/10 g
Accuracy	Certified according OIML R51 Y (a)
Throughput	1.500 pph up to 4.000 pph, for one scale; 6.000 pph up to 8.000 pph, for dual in-line scale
Product	Parcel and Flats; 100 mm x 100 mm x 5 mm; 1.500 mm x 1.000 mm x 1.000 mm
Speed	Certified up to 2 m/s, max 2,8 m/s
Interface	RS 232, RS 422, RS 485, Profibus, Ethernet
Periphery	Possible in combination with DWS, Alibi storage

